

IRD WITH ANSWERING MACHINE AND REMOTE RECORDING EVENT  
PROGRAMMING

Field of the Invention

[0001] The present invention relates to the field of video recorder device programming and, more particularly, to a set-top box with the capability of receiving and transmitting program data for a video recorder to a remote user.

Background of the Invention

[0002] In common use today is a set-top box used to control reception and display of video data. Also common today is programming of video recorder devices. While there is still a large installed base of set-top boxes designed to receive only analog signals, set top boxes designed to receive digital signals are becoming more popular. Furthermore, not only are digital signals received via satellite systems, cable systems are upgrading to the transmission of digital signals in greater numbers.

[0003] Most currently available set-top boxes are equipped with a feature that allows the set-top box to make outgoing telephone calls through a telephone port. This port is always connected and is used, for example to telephone the service provider to download billing information or to request pay-per-view programming.

[0004] This telephone connection may also be used to program a device, for example, a VCR, to record a particular program from a remote location. An example of a programming device using an ordinary telephone connection is disclosed by Hashimoto in U.S. Patent 5,420, 913. A common telephone is linked through the device to a video recorder. A user may call the telephone from a remote site and, using telephone keypad at the remote site, enter PlusCodes or other reservation codes into the recording device, which may or may not be in the set-top box. As such, this invention may require special hardware for implementation. Also, a user can only program the recorder device with the codes. Should a user not know the code of the show he or she is seeking, or if the user wishes to program a device to start or stop

09909179-071904  
F06T20-610US

[0005] recording at some time other than that specified by the code, this device cannot be used.

### Summary of the Invention

[0006] It would be advantageous to incorporate an answering machine into the set top box. In that manner, the answering machine would be able to "answer" the telephone and interact with the remote user. In a special mode, the user can remotely check the status of pending programs and can program either the box or an associated video recorder to start and stop at any time. Furthermore, off-the-shelf components can be used to construct the device. Therefore, there is a need for a set-top box with answering machine functions so that a user may program the set-top box or associated video recorder without the need for special equipment. Also, the user may program his audio/video equipment from any location where a telephone is available.

[0007] The present invention includes a method and apparatus for programming a video recording device from a remote location. The device includes a microprocessor, an infrared signal transmitter electrically coupled in the microprocessor, a telephone answering device, and a memory device. A user can call the programming device through the telephone device and enter a code through a telephone key pad which puts the device in programming mode. The microprocessor then takes control from the answering device and, using the telephone key pad, a user can enter commands that the microprocessor understands as programming commands. These commands can be stored and/or transmitted to a video recorder for processing.

### Brief Description of the Drawing

[0008] FIG. 1 is a block diagram of an exemplary embodiment of the present invention.

[0009] FIG. 2 is a block diagram of an IRD of an exemplary embodiment of the present invention.

09509179-074901  
FOI b7c b7d

[0010] FIG. 3 is a block diagram of an answering machine module in an exemplary embodiment of the present invention.

[0011] FIG. 4 is a block diagram of an infrared control module in an exemplary embodiment of the present invention.

[0012] FIG. 5 is a flow chart of an exemplary embodiment of a programming mode of the present invention.

[0013] FIG. 6 is a flow diagram of an exemplary embodiment of an EP program mode of the present invention.

[0014] FIG. 7 is a flow diagram of an exemplary embodiment of an EP delete mode of the present invention.

[0015] FIG. 8 is a flow diagram of an exemplary embodiment of an EP edit mode of the present invention.

### Detailed Description of the Invention

[0016] FIG. 1 shows a high level block diagram of an exemplary embodiment of a set-top box (STB) 10 according to the present invention. The STB 10 includes an answering machine module 12, an infrared interface 14, a memory 16, a digital television (DTV) integrated receiver/decoder (IRD) 18, a control keypad 17, a display 19, a communications interface 20 and a video output port 24 and a video input port 26. The answering machine module 12 performs basic answering machine functions such as on-hook and off-hook detection, greeting message playback, message recording and message playback. Linked to the answering machine module 12 by a control bus 22 is the digital television IRD 18. The IRD performs the functions required to receive and display a digital television signal. Typically, these functions include receiving a digital signal, performing all required signal conditioning, and transmitting a display signal to a display device such as a television monitor (not shown).

106720-62760660

09909179-071901

[0017] The IRD 18 also controls the programming function of the set-top box 10. The infrared interface 14 is linked to the IRD 18 and functions as a transmission device to transmit programming commands to a VCR or other video recording apparatus that has the ability to receive coded IR signals from a remote device. The infrared interface 14 may be, for example, an IR blaster such as used by VCR plus® units. Storage 16 is internal storage such as a magnetic disc, SD memory modules, or some other form of non-volatile memory. Preferably, storage 16 is a high capacity device. Storage 16 may store command functions for the infrared interface 14 only or, in an alternative embodiment, may record the requested television program in the manner of a personal video recorder such as that manufactured, for example, by REPLAY TV. The answering machine module 12 and the IRD 18 communicate to a user via the communications interface 20 which, in an exemplary embodiment, may be a standard serial or parallel communications port as used in any common personal computer. Also, the STB 10 includes an industry standard video input port 26, for receiving video from a cable provider, satellite system or video playback device, and an industry standard video output port 24 for transmitting a video signal to a display device or a recording device.

[0018] FIG. 2 is a block diagram of an exemplary embodiment of the IRD 18 of the set-top box of the present invention. The primary microprocessor 28 performs all of the basic computing and control functions required for operation of the STB 10. In this exemplary embodiment, the microprocessor 28 receives and transmits data through the host interface 30. In the exemplary embodiment of the invention, the host interface 30 may be, for example, an IEEE 1394 "firewire" bus. This information may include, for example, control signal data received from the answering machine module 12. This information may also includes programming received from the video recording device via the 1394 bus or data transmitted to the recording device via the IR interface 14. Alternatively, the IR interface may be coupled to the microprocessor 28 directly. Of particular interest to the present invention, when the answering machine module 12 receives the proper code, the system is placed in event programming (EP) mode.

[0019] The module 12 passes control to the IRD 18, at which time the primary microprocessor 28 then prompts the user through the telephone connection for

[0020] programming data. The microprocessor 28 receives the data, processes it and transmits it to memory 34 where the data is stored. In an alternative embodiment, the processed programming data may be transmitted directly back through the host interface 30 or to the IR interface 14, where the data is broadcast to a video recording device via the IR blaster. When the programming data is stored, the microprocessor 28 determines when the start time and date contained in the programming data equals the present time and date and sends a message with the appropriate tuning and recording commands for the VCR or other recording device to the host interface 30 or to the infrared interface 14. Alternatively, the microprocessor 28 may send a command to the tuner and demodulator 32 of the IRD 18 to tune to the proper channel and provide the received signals to the recording device through the video output port 24 or to the storage module 16 of the STB 10 (shown in Fig. 1).

[0021] FIG. 3 is an exemplary embodiment of the answering machine module 12 of the present invention. The module 12 contains an answering machine 35 which has a communication interface 37 coupled to an industry standard public switched telephone network (PSTN) 39. The module 12 functions in the following manner: When a user connects to the answering machine 35 through the PSTN, the answering machine 35 senses the ring signal, places the answering machine in an off-hook condition, and sends the greeting message. While sending the greeting message, the answering machine 35 is also waiting to receive the event programming (EP) code. Once the user enters the EP code, the answering machine passes control to the IRD 18 and the system is put in event programming mode (EP mode). Otherwise, the answering machine 35 continues as an industry standard answering machine. The operation of the system in EP mode is described below with reference to Figs. 6, 7 and 8.

[0022] FIG. 4 is an example of an embodiment of the infrared interface device 14 of the present invention. The IR host interface 42 receives programming data from the IRD 18 and sends the data to the code processor 44. The code processor 44 may contain, for example, product codes and corresponding infrared pulse patterns for many commercially available video recorder devices with IR interfaces. The programming data is converted to the proper infrared pulses for the selected device which are broadcast to the video recorder via the infrared transmitter 46. The infrared

09909179-071901

[0023] transmitter 46 is placed in a direct line of sight to the infrared receiver of the video recording device so that the video recording device may be controlled by the infrared pulses. In an alternative embodiment, if the infrared interface 14 is an IR blaster, the infrared receiver need not be in direct line of sight.

[0024] FIG. 5 is a flow diagram that is useful for describing an exemplary embodiment of the communication function of the present invention. At step 100, the answering machine detects an incoming call. At step 102 the call is answered and the answering machine plays a normal answering machine greeting. At step 104 the answering machine determines if the event programming code has been detected while or after the greeting was played. In the exemplary embodiment of the invention, the event programming code is a specific sequence of dual-tone multi-frequency (DTMF) tones, for example, "##." The code may be entered by the remote user on the telephone keypad.

5.6 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000

[0025] If, at step 104, the event programming code is detected, at step 106 the answering machine unit transmits a signal to the microprocessor to enter event programming mode and, at step 108, passes control to the IRD 18. If no event programming code is detected at step 106 then, at step 110 the answering machine determines if the end of message has been played. If not, the answering machine unit returns to step 104 and continues "listen" for an EP code. When the end of message code is been detected at step 110, step 112 the answering machine unit may wait, for example, for a short interval (e. g. two (2) seconds) before continuing. After the delay, if no EP code is detected, the answering machine unit functions strictly as a standard answering machine. It may, for example, prompt the user to leave a message or enter a code to place the answering machine into answering machine administrative mode, allowing the user to retrieve messages or perform administrative functions.

[0026] In an alternative embodiment, once the EP code is detected, the system prompts the user to enter a code for programming mode or another code for answering machine administrative mode, so that a user need not wait for the end of the greeting message to enter answering machine administrative mode.

[0027] FIG. 6 is flow-chart diagram of an exemplary embodiment of the EP store program mode of the present invention. At step 202, the answering machine module 12 detects the EP code entered by the user, and the system enters EP mode. At step 203, the user selects the device to be programmed as the user may have multiple recording devices, for example, a VHS VCR, a digital VCR (DVCR), or a personal video recorder. At step 204, the user is prompted to indicate an action, for example, store a new program, delete a program or review and edit a program. The prompts may be accomplished, for example, by a speech synthesizer (not shown) in the answering machine module 12 which announces the choices in a menu format.

[0028] If, at step 204, the user has selected the store option, then, at step 206, the system prompts for a start time for recording. The user then enters the requested data on the telephone keypad. The system 10 detects the DTMF codes, converts the DTMF into programming data, and, at step 208 receives and stores the data in memory. At step 212, the system prompts for a channel to be recorded. In the same manner as step 208, at step 214 the system receives and stores the programming data. In the same manner as the start time and channel data, at steps 216 and 218 the system prompts the user for a stop time. In an alternative embodiment, instead of a stop time, the user may enter a time for duration of the recording. Time may be entered in one of two ways; either hour, minute and am/pm, or in military form, such as x00 hours.

[0029] In order to allow programming of events that will occur on future days, months or years, and also to limit programming steps, the system 10 interprets data entered in response to a time prompt, and uses certain defaults. If only a time is entered, the day, month and year defaults to the next available day for the time specified. For example, if 0800 is entered by the user at step 206, and the entry is made at 1000 hours, the system interprets the time as 8:00 am the next day. Alternatively, if 0800 is entered by the user, and the entry is made at 0600 hours, the system interprets the time entered as 8:00 am on the day the time was entered. Furthermore, if time and date are entered, but not month and year, the current month and year are assumed. Lastly, if time, date and month are entered without a year, the current year is assumed.

09909179-071901

[0030] At step 230 the system then determines if there is sufficient storage space to store the required program. Prior to using the system, a user can input, through the front panel controls 17, a code which identifies the connected storage device and, if necessary, the recording mode. From this, the system can determine how many total minutes of video information can be stored. As each program is entered, the system can determine how many total minutes are available on the recording medium, and can inform the user if the total capacity is exceeded. If the STB 10 is coupled to the recording device by a control bus such as the IEEE 1394 bus, the available amount of time can be determined by interrogating the recording device. Otherwise the amount of time can be estimated if, for example, the user resets a counter in the STB for the recording device when the tape is rewound. By default, the system records the requested programming on the VCR or other external video recorder. If the tape in the VCR is full, the system may record the requested video programming on the mass storage 16 (shown in Fig. 1). The user can also select to record over video data in the mass storage, or to append only. Although not shown in Fig. 6, if the maximum capacity is exceeded by the program request, the user can choose to rewind the tape to record over previously recorded material or may edit existing programs for the recording device to correct the condition at step 232.

[0031] Once the programming sequence is complete, at step 234, the user is prompted either to continue in EP mode, or exit. Once the user exits, control of the communication is passed back to the answering machine module 12. Furthermore, an escape code, such as "##", may be used at anytime in EP mode to return the user to step 202. Another escape code may be used at anytime to return the user to answering machine mode.

[0032] In this exemplary embodiment, the programming data is stored and transmitted, as a serial string of data. An exemplary embodiment of the timer message format may be as follows: stttmmddyyyyzaaaacxxxx. In this implementation, the string "stttmmddyyyy" signifies start time data, with the time in military form, followed by the month day and year. "zaaaa" signifies duration of the recording as "aaaa" minutes. The "cxxxx" represents the channel number "xxxx." Alternatively, the timer message could be: stttmmddyyyyzttttmmddyyyycxxxx, where

09909179.074901  
T06T20" 62T60660



[0033] "s" and "c" are the same as above, but "z" would be end time, and is represented similar to the start time. As an exemplary embodiment, s080001012002z0300c0100 represents a program code of: start recording on January 1, 2002 at 8:00 am, record for 300 minutes and record channel 100.

[0034] As shown in Figure 6, at step 204, the system prompts a user to indicate if a record program, delete program or edit program mode is required by pressing, for example, the "7" key for record, the "3" key for delete and the "\*" key for edit. If the delete function is selected, the unit is placed in the delete program mode, as shown in the exemplary flow-chart diagram of Figure 7. At step 250, the system enters program delete mode. At step 252, using the speech synthesizer, the system announces each program that is stored in memory. For example, a typical announcement may be "program 1, channel 35, start time 1:00 p.m., end time 3:00 p.m." At step 254, after each program the user may be prompted to indicate if the program is to be deleted. A typical prompt may be, for example, "Delete this program? Press "9" for yes, "6" for no." If the user selects the proper key for "yes" on the telephone keypad, the program is erased at step 256. If the program was not stored but was broadcast to the recording device using the IR blaster, the IR blaster may be used to send commands to the recording device to cancel the prior commands. If, at step 254, the user indicates "no" or after the program has been deleted at step 256, then, at step 258, the system determines if there are any other programs to announce. If the last program had been announced, the system exits EP delete mode at step 260. If there are other programs in memory that have not been announced, at step 262 the system prompts the user if the user would like to delete another program. If "yes", the system returns to step 252. If no, the system exits EP edit mode and return to the "enter, delete or edit program" step, 204.

[0035] If the edit program selection is made at step 204 in Fig. 6, the system enters an EP edit mode. An exemplary embodiment of the EP edit mode is shown in the flow-chart diagram of Fig. 8. At step 280 the system enters EP edit mode. Similar to the EP cancel mode described above and illustrated in Figure 7, at step 281 the system announces each program to the user. At step 283, the system prompts the user to indicate if the user desires to edit the announced program. If "no", the system

0909179-071901  
T06T20-6ZT60660

[0036] determines if there are any other programs which have not been announced and, either returns the user to step 281, or exit EP edit mode at step 292.

[0037] If the response to step 283 is "yes", at step 282 the system announces each parameter of the program and prompts the user, after each announcement, to indicate if the user wishes to edit the announced parameter. The parameters are, for example, start time, end time, date and channel, for each program. If a "yes" response is received, at step 286, the system prompts the user for a new value for the announced parameter and update the memory accordingly. If "no", and after each edit, at step 288, the system determines if it has prompted for all the parameters of program. If not, the system returns to step 282 to continue prompting the user. When the last parameter is reached, at step 290, the system prompts the user to indicate if another program is to be edited. If yes, the system returns to step 282 to continue to the next parameter, until all parameters are prompted for each program. If the user enters "no" at step 290, the system exits EP edit mode at step 292.

[0038] Although not described above, it is contemplated that the IRD 18 may confirm any entry made by the user immediately after that entry is made by converting the entry to speech and asking the user to confirm that the entry is correct. In addition, although the described embodiments allow the user to enter only the channel number, the start time and the stop time or duration, it is contemplated that other commonly used options may be added to the list of parameters, for example, recording speed and whether the program is a weekly program, a daily program or a single event.

[0039] In an alternative embodiment, the user may enter EP edit mode or EP cancel mode after each program is announced. In this manner, the system can inform the user of the parameters of each program and allow the user to select whatever EP function the user requires for each program.

[0040] Although the invention has been described in terms of exemplary embodiments, it is contemplated that it may be practiced as described above with variations that are within the scope of the following claims.

09909179-074901  
FOI b7c b7d b7e b7f b7g b7h b7i b7j b7k b7l b7m b7n b7o b7p b7q b7r b7s b7t b7u b7v b7w b7x b7y b7z